

0.75KW Gasoline Generator

This gasoline generator provides a reliable power output for various applications. Featuring a 2HP 2-stroke engine, it is engineered with safety features and a user-friendly interface.

KJ950A
Type: Brushless, Revolving Magnetic Field, Self-exciting, 2 Poles, Single-phase
Frame: 612mm Steel Tube
Rated AC Output: 0.65KW
Max AC Output: 0.75 KW
Frequency: 50Hz
Voltage: 220~240V
Voltage Regulator: Condenser
Power Factor: Cosφ = 1.0
Engine
Model: 1E43F 2.0HP
Type: Forced Air-cooled, 2-Stroke, single cylinder, Reed Valve
Bore × Stroke: 42mm × 42mm
Displacement: 63ml
Recommended Fuel: Unleaded Gasoline
Fuel tank capacity: 4.2L
Fuel consumption: 544g/KWhour
Engine Oil Capacity: Gasoline and Oil mixing ratio 40:1
Start Mode: Recoil and hand-operated
Standard Features
Oil Alert: without
Fuel Gauge: without
AC Voltmeter: without
Indicator Light: with
AC Circuit Breaker: with
Electric Starter: without
Option
DC outlet(12V/8.3A): with
DC Circuit Breaker: with
Frame Pallet: with
Battery(12V 4.5Ah): without
Handle: without
Wheel: without

ADDITIONAL IMAGES



Overview

Compact Power Solution

The KJ950A is a compact and robust gasoline generator engineered for reliable performance in both residential and commercial settings. Featuring a 2HP 2-stroke engine, this unit is ideal for emergency backup power, outdoor recreational activities, and running small tools or appliances. Its user-friendly interface and durable steel tube frame ensure ease of operation and long-lasting utility.

Key Performance Metrics

0.75 KW

Max AC Output

0.65 KW

Rated AC Output

2 HP

Engine Power

Electrical Specifications

Electrical Technical Details

Parameter	Value
Voltage	220~240V
Frequency	50Hz
Power Factor	1.0
Voltage Regulator	Condenser
Phase	Single-phase

Engine Specifications

Engine Configuration

- Model: 1E45F
- Type: Forced air-cooled, 2-stroke, single cylinder
- Displacement: 63ml
- Bore x Stroke: 45mm x 42mm
- Start Mode: Recoil and hand-operated

Fuel and Operation

Fuel & Consumption

- Fuel Type: Unleaded Gasoline
- Mixing Ratio: 40:1 (Gasoline to Oil)
- Tank Capacity: 4.2L
- Fuel Consumption: d544g/KW-hour

Features and Options

Standard Features

Indicator Light • AC Circuit Breaker • Steel Tube Frame (112mm)

Available Options

DC Socket (12V/8.3A), DC Circuit Breaker, Foam Packing

Certifications

CE