

# 1 Gang Single/2 Way Surface Mount Light Switch

This surface-mounted switch supports both single and two-way operation. Constructed from durable, fire-resistant thermoplastic, it is suitable for residential and commercial applications.



## Product Overview

### Robust Surface-Mounted Switching Solution

This 1-gang surface-mounted switch is engineered for versatility and durability in demanding environments. Featuring an IP65 rating for dust and water protection, it is constructed from fire-resistant, UV-stabilized thermoplastic to ensure long-term reliability. With a modular design and multiple terminal options, this switch is suitable for both residential and commercial electrical installations requiring high safety standards.

## Technical Specifications

### Ingress Protection

IP65

Fire Resistance Rating	850
Dielectric Strength	2000 V
Tested Lifetime	40000 cycles
Operating Temperature Range	-15 to 45 °C
Storage Temperature Range	-20 to 50 °C

## Compliance & Quality

### Warranty Period

**10 years**

Mechanical Switch/Socket

**2 years**

Electronic Items

### Certifications

TUV, CE, RoHS

## Installation & Design

### Terminal Options

- Screw Terminal
- Screw-less Terminal

### Mounting Orientation

- Vertical
- Horizontal

Material	PC-UV Thermoplastic (Halogen-free)
Cable Capacity	Æ4-Æ20