

10AX 3-Gang One-Way Wall Switch with Hanger

This 10AX wall switch features a three-gang, one-way configuration. It is constructed from fire-resistant PC material and has an optional removable hanger.



Overview

Modern 3-Gang Wall Switch

This 10AX 3-gang one-way wall switch features a classic, simple design with a large push-button interface for an elegant and noble feel. Built with fire-resistant PC material capable of withstanding 850 , it ensures high safety standards for residential and commercial environments. The modular fitting design allows for flexible combinations, while the optional hanger provides versatile installation choices to meet specific project needs.

Technical Specifications

Electrical Ratings

10 AX

Rated Current

250 V~

Rated Voltage

60 Hz

Max Frequency

Network Frequency	50/60Hz
Switch Function	3 Gang 1 Way (Mechanism supports 2 way)

Design & Construction

Construction Materials	Fire-resistant PC, TPE, Brass, K200 Silver Contacts
Surface Finish	Glossy Button / Matt Enclosure
Actuator	Rocker

Installation

Mounting & Wiring

- Surface mounting
- Screw terminal fixing
- Removable hanger option
- 10mm wire stripping length
- 1.5-2.5mm² rigid wire capacity

Dimensions (with Hanger)	86 x 86 x 45 mm
--------------------------	-----------------

Durability & Safety


Safety Tests

- 850 Fire resistance test
- 2000V Dielectric Strength test
- >3mm Opening distance


Service Life

40000 Cycles

Compliance & Applications



Compliance with Low Voltage Directive 2014/35/EU for electrical safety.



TUV SUD certified rocker switches ensuring international quality standards.

Certifications

CE • TUV • ISO 9001 • ISO 14001

Recommended Use

Residential, Hotel, School, Bar, Exhibition Centers