

1350W Epoxy and Polyurethane Foam Injection Pump

This 1350W grouting machine is designed for injecting epoxy and polyurethane foams into concrete structures. It is suitable for crack repair, sealing, and waterproofing applications.



Overview

Professional Concrete Repair Solution

This 1350W high-pressure grouting machine is a specialized tool designed for waterproof epoxy and polyurethane foam injection. It is engineered to effectively repair house cracks and seal concrete structures by injecting materials deep into voids to prevent leakage. Built for durability and professional use, it offers a reliable solution for maintaining structural integrity in demanding construction environments.

Technical Performance



The 1350W motor provides high-pressure output for deep crack penetration and effective waterproofing.

Performance Metrics

1350 W

Motor Power

15000 psi

Max Output Pressure

8 kg

Machine Weight

Pressure Specifications

Parameter	Value
Restart Pressure	3000 ~ 10000 psi
High-Pressure Pipe Burst Pressure	10000 psi
Switching Valve Safe Range	18000 psi

Power & Compatibility

Electrical Requirements

- Voltage: 110V ~ 240V
- Frequency: 50/60Hz
- Power Adapter support for US, Canada, UK, Spain, Australia, Brazil, Chile, Russia, Indonesia, Thailand, Philippines, Japan

Application & Materials

Compatible Materials

Epoxy Resin, Polyurethane Foam, Waterproofing Grout

In the Box

Included Accessories

- High Pressure Hoses
- Wrenches
- Protective Glasses
- Injection Tips
- Wearing Parts
- Power Adapter

Service & Reliability

Service Commitments

24 Months Guarantee • Free Technical Consult • 5+ Years Lifetime Expectancy