

13L Forced Exhaust Gas Water Heater

This 13L gas water heater provides on-demand hot water with a forced exhaust system. It has adjustable settings for gas input and water flow, along with a digital temperature display.



ADDITIONAL IMAGES



Product Overview

High-Efficiency Domestic Hot Water Solution

This 13L forced exhaust gas water heater is engineered for reliable, on-demand hot water delivery in residential settings. Featuring a forced exhaust system for enhanced safety and efficiency, the unit includes precision controls for gas and water flow. The integrated digital display provides real-time temperature monitoring, ensuring consistent performance for household needs.

Performance Metrics

Rated Heat Loading

26 KW

Rated Heat Loading

Hot Water Capacity

13 kg/min

Rated Capacity

Technical Specifications

Gas Pressure Requirements

Gas Type	Rated Pressure
LPG	280 Pa
NG	2000 Pa
TG	1000 Pa

Model Number JSQ26-13MA

Supported Gas Types LPG, NG, TG

Installation & Dimensions

Dimensions	650 x 400 x 190 mm
Flue Pipe Diameter	50 mm
Applicable Water Pressure	0.02MPa - 0.8MPa

Features

Safety & Control Features

- Forced exhaust system
- Overheat protection
- Flame failure detection
- Digital temperature display
- Adjustable gas flow control
- Adjustable water flow control