

1t x 2m Eye-and-Eye Polyester Webbing Sling

This 1-ton by 2-meter webbing sling is made from 100% polyester. It features reinforced eyes for secure attachment and is compliant with CE and GS safety standards.



ADDITIONAL IMAGES



Product Overview

High-Tenacity Polyester Webbing Sling

This 1t x 2m eye-and-eye webbing sling is manufactured from 100% high-tenacity polyester, providing exceptional durability and resistance to abrasion. Designed for professional lifting applications, it features reinforced eyes for secure attachment and is compliant with international safety standards. Its lightweight yet high-strength construction makes it an ideal choice for various industrial and construction settings.

Key Performance Metrics

1000 kg

Working Load Limit

2 m

Length

5 :1

Safety Factor

Technical Specifications

Material	100% High-tenacity Polyester
Configuration	Eye-and-Eye
Webbing Width	25 mm
Approx. Thickness	7.5 mm
Eye Length	350 mm
Weight per Meter	0.19 kg

Compliance & Safety

Certifications

CE • GS • TÜV Rheinland

Product Range

Webbing Sling Series Data

Art No.	WLL (kg)	Width (mm)	Eye Length (mm)
W01-01	1000	25	350
W01-02	2000	50	400
W01-03	3000	75	450
W01-04	4000	100	500
W01-05	5000	125	550