

25A Modular Contactor 230V Coil

This contactor range satisfies most application needs. These contactors can be combined with auxiliary control, protection, and indication functions and are available with or without manual operation.



Product Overview

Versatile Modular Contactor

This 25A modular contactor is engineered for reliable remote control applications across residential, commercial, and industrial networks. It supports a variety of loads, including lighting, heating, ventilation, roller blinds, and sanitary hot water systems. Designed for flexibility, the unit is available in both manually-operated and non-manually-operated versions, allowing for seamless integration into load-shedding and control circuits.

Electrical Ratings

Rated Operational Current (Ie)

25 A

Rated Current

Utilization Category

AC-7a

| | |
|--------------------------------|-----------------|
| Coil Voltage | 230V AC 50/60Hz |
| Rated Operational Voltage (Ue) | 250 V |
| Rated Insulation Voltage (Ui) | 500 V |

Compliance & Standards

| | |
|-----------|-----------------------|
| Standards | EN61095, IEC61095, CE |
|-----------|-----------------------|

Features

Typical Applications

- Lighting control
- Heating systems
- Ventilation systems
- Roller blinds
- Sanitary hot water
- Load-shedding of non-priority circuits

Design Features

- Compact modular design
- Screw terminals for easy wiring
- Clear contact position indication
- Available with or without manual operation