

# 3-Pole 40A Electronic AC Contactor 24-277V

This 3-pole contactor is rated for 40A with a coil voltage of 24-277V. It is commonly used for refrigeration, air conditioning, and heating applications.



## ADDITIONAL IMAGES



## Product Overview

### Reliable HVAC Switching

This 3-pole definite purpose contactor is engineered for consistent performance in demanding HVAC and refrigeration systems. Designed to break all lines, it provides safe and efficient control for hermetic compressors and other resistive loads. Built to international standards, this contactor offers durability and ease of installation for professional electrical setups.

## Electrical Ratings

### Ampere Rating

**40 A**

Resistive Load

**30 A**

Full Load Amps (FLA)

Number of Poles	3
Maximum Voltage	600 V
Coil Voltage	24V AC (50/60 Hz)

## Performance Standards

### AC Operating Ratings

Category	Amperage	Voltage
AC-1	20	277
AC-3	15	277

Standards	IEC60947-4-1, CE
-----------	------------------

## Installation

### Terminal Torque Specifications

- Screws: 22 in-lbs
- Lugs: 40 in-lbs

## Service & Logistics

### Order Terms

- OEM/ODM available
- 15-20 days delivery time
- 30% deposit required
- Free samples available (shipping costs apply)