

3-Pole Contactor 30A

This 3-pole contactor is designed for HVAC and refrigeration applications. It is rated for 30A and features silver cadmium oxide contacts for reliable switching of electrical circuits.



ADDITIONAL IMAGES



Product Overview

Industrial Contactor Overview

This 3-pole SA Series contactor is engineered for robust performance in HVAC and refrigeration applications. It provides reliable control for compressors, fans, and motor-driven equipment across diverse industrial environments. Built for durability, it features high electrical and mechanical endurance, ensuring long-term operational consistency.

Electrical Specifications

| | |
|---------------|-----------------|
| Rated Current | 30 A |
| Voltage Range | 24V-480V |
| Coil Voltage | 24V AC 50/60 Hz |

Performance Metrics

Key Performance Metrics

| | | |
|---|---|--|
| 250000 cycles Electrical Life (Resistance Load) | 100000 cycles Electrical Life (Horsepower Load) | 1000000 cycles Mechanical Life |
|---|---|--|

Technical Standards

Recommended Torque (CU 75°C)

| Component | Torque Value |
|-----------|--------------|
| Screws | 22 in-lbs |
| Lugs | 40 in-lbs |

| | |
|----------------|------------------|
| Certifications | CE, IEC60947-4-1 |
|----------------|------------------|