

3-Pole Electrical Contactor 24V

This 3-pole contactor is designed for switching electrical circuits. It has a 24V 50/60Hz coil and auxiliary contacts 13 NO and 14 NO.



ADDITIONAL IMAGES



Overview

High-Performance 3-Pole Contactor

This 3-pole electrical contactor is engineered for reliable remote switching of power circuits in demanding industrial environments. Designed for efficiency and safety, it features a 24V coil voltage and is suitable for high-power electrical appliance control, including central air conditioning systems. The unit complies with international standards, ensuring robust performance and durability for professional electrical applications.

Electrical Ratings

Coil Voltage	24 V
Rated Insulation Voltage (Ui)	690 V
Rated Thermal Current (Ith)	25 A

Performance Metrics

AC3 Power Ratings

4 kW 220/230V	5.5 kW 380/415V	5.5 kW 660/690V
-------------------------	---------------------------	---------------------------

AC3 Rated Current	7.9 A
-------------------	-------

Compliance & Standards

Certifications & Standards	IEC 60947, GB 14048.4, VDE 0660, CE
----------------------------	-------------------------------------

Technical Details

Terminal Layout

Function	Terminals
Main Input	1 L1, 3 L2, 5 L3
Main Output	2 T1, 4 T2, 6 T3
Auxiliary Contacts	13 NO, 14 NO

Model Number	LC1-D1210
---------------------	-----------