


35kV Self-Amalgamating Insulating Tape

This self-amalgamating tape is rated for use up to 35kV, making it suitable for high-voltage applications. It bonds to itself when wrapped under tension, creating a waterproof and airtight seal for insulating electrical connections, cables, and joints.



ADDITIONAL IMAGES



Product Overview

High-Performance Self-Amalgamating Tape

This 35kV self-amalgamating rubber tape provides a versatile solution for professional electrical insulation, waterproofing, and splicing applications. Designed to fuse with itself when stretched and overlapped, it creates a seamless, void-free, and highly flexible rubber molding. With exceptional resistance to water, UV, and ozone, it is ideal for protecting cable connections in both permanent and temporary environments.

Technical Parameters

Thickness	0.76 mm
Tensile Strength	1.3 Mpa
Elongation at Break	700 %
Disruptive Strength	16 kV/mm

Key Features

Performance Characteristics	Waterproof, UV Resistant, Ozone Resistant, Self-Fusing, Clean Removal
-----------------------------	---

Availability Options

Available Widths

- 18mm
- 19mm
- 25mm
- 38mm
- 50mm

Available Lengths

- 2m
- 5m
- 9m
- 10m

Applications

Primary Applications

- Communications cable connections
- Pipeline protection
- High-voltage cable splicing (up to 35kV)
- Temporary insulation
- Moisture-proof sealing