

# 35L Dispersion Kneader

The 35L dispersion kneader features an advanced design and imported core components. It excels in sealing, safety, abrasion resistance, stability, and precise temperature control for bulk production.



## ADDITIONAL IMAGES



## Product Overview

### Industrial Dispersion Kneader

The 35L Dispersion Kneader utilizes advanced international design principles to deliver superior mixing performance for natural rubber, synthetic rubber, and modified plastics. Engineered for durability, the chamber features a specialized abrasion-resistant coating that significantly extends service life compared to traditional models. With precise temperature control and high-torsion drive systems, this machine ensures consistent, efficient production for demanding industrial applications.

## Technical Specifications

### Mixing Capacity

**35 L**

Mixing Capacity

**60 KG/load**

Max Productivity

### Motor Power Ratings

Component	Power Rating
Driving Motor	55
Tilting Motor	2.2
Electric Heater	10

### Dimensions & Weight

- Dimensions (H x W x L): 3,200 x 1,900 x 3,000 mm
- Weight: 6,500 KG
- Tilting Angle: 140°

## Features & Construction

### Operational Advantages

High Abrasion Resistance • Low Noise Operation • Energy Efficient • Easy Maintenance

### Engineering Highlights

Chromium-coated Chamber, 42 Cr-Mo Gear Reducer, Hardened Tooth Surface, Dry Mechanical Shaft Seal, Reverse Rotation Discharge