

# 3T x 2M Polyester Webbing Sling

This webbing sling is made from high-quality synthetic fiber using advanced weaving technology. It adheres to international standards, with a load range from 0.5t to 50t and safety factors of 4:1, 5:1, 6:1, 7:1, and 8:1, according to customer requirements.



## ADDITIONAL IMAGES



## Product Overview

### High-Strength Polyester Webbing Sling

This 3-ton polyester webbing sling is engineered for professional lifting applications, offering a balance of high strength and flexibility. Constructed from 100% high-tenacity polyester with a double-ply layer, it ensures reliable performance and durability in demanding industrial environments. The sling features reinforced folded eyes and is designed to meet international safety standards for secure load handling.

## Performance Metrics

### Key Performance Metrics

**3 t**

Working Load Limit

**6 :1**

Safety Factor

**75 mm**

Webbing Width

## Technical Specifications

### Detailed Dimensions

Parameter	Value
Width	75mm
W.L.L.	3t
Safety Factor	6:1
Layer	Double ply
Material	100% high tenacity polyester
Construction	Double ply
Length	3 m
Lifting Eye Type	Folded Eye

## Compliance & Standards

### Standards Compliance

- EN1492 Standard
- Color coded according to EN standards

### Certifications

CE • TUV Rheinland • GS • Geprüfte Sicherheit