

3T x 3M Polyester Webbing Sling

This 3-ton by 3-meter lifting sling is made from high-strength polyester webbing. It is designed with a 7:1 safety factor and certified to CE and GS standards.



ADDITIONAL IMAGES



Overview



High-Strength Polyester Webbing Sling

This 3T x 3M polyester webbing sling is engineered for heavy-duty industrial lifting, featuring a high safety factor of 7:1. Constructed from 100% polyester, it offers excellent durability and resistance to abrasion while remaining gentle on the load surface. Certified to CE and GS standards, it provides a reliable and secure solution for construction, manufacturing, and logistics applications.

Key Performance Metrics



Lifting Performance

3 T

Working Load Limit

3 M

Length

7 :1

Safety Factor

Technical Specifications



Available Ply Types

- Single ply flat webbing
- Double ply flat webbing
- Three ply flat webbing
- Four ply flat webbing
- Flat webbing with metal fittings

Material

100% Polyester Webbing

Sling Eye Variations

Flat Eye, Reverse Eye, Folded 1/2, Folded 1/3

Safety & Compliance

Certifications

CE • GS • TÜV Rheinland

Safety Guidelines

- Inspect for damage before each use
- Protect webbing from sharp edges
- Do not exceed rated lifting capacity
- Avoid contact with acid, alkali, and sunlight
- Do not tie knots in sling webbing
- Use only if trained

Reference Data

Model W01-01 Reference

Metric	Value
Working Load Limit	1000 kg
Approx Thickness	7.5 mm
Approx Width (5:1/6:1)	25 mm
Eye Length	350 mm
Weight per Meter	0.19 - 0.22 kg