

400A Molded Case Circuit Breaker

This molded case circuit breaker is rated for 400A and designed for electrical distribution. It has a rated insulation voltage of 690V, impulse withstand voltage of 8kV, and complies with IEC60947-2 standards.



Overview

High-Performance Molded Case Circuit Breaker

This 400A Molded Case Circuit Breaker (MCCB) is engineered for reliable electrical distribution and circuit protection. Designed to meet international IEC/EN 60947-2 standards, it offers robust performance with a rated insulation voltage of 690V and an impulse withstand voltage of 8kV. Available in 3 and 4-pole configurations, this device ensures safety and operational efficiency in demanding industrial and commercial electrical systems.

Electrical Ratings

Rated Current

400 A

Rated Current

690 V

Insulation Voltage

8 kV

Impulse Withstand

Rated Working Voltage

400/415 AC V

Performance

Breaking Capacity (Icu)

Voltage (AC V)	Breaking Capacity (kA)
220/240	55
400/415	40
660/690	25

Service Breaking Capacity (Ics)

75% of Icu

Standards & Compliance

Certifications

IEC 60947-2, EN 60947-2, CE, KEMA

General Specifications

Pole Configuration

- 3-Pole
- 4-Pole

Frequency

50/60 Hz

Ambient Temperature

40 °C