

Adjustable Industrial Blower Fan

This adjustable blower fan is designed for industrial and commercial applications requiring high-volume air movement. The blower features a robust construction with a durable metal housing and adjustable stand for precise airflow positioning.

性能參數表 Technical Data Sheet

| 型號 | 規格 | 風量 | 轉速 | 功率 | 噪音 | 風壓 | 風速 | 風量 | 噪音 | 淨重 |
|-----------|----------|--------|-------|-------|--------|-----------|-------------------|------|-------|----------|
| Model | Size(mm) | (m³/h) | Phase | (Hz) | (W) | (r/min) | Capacity (m³/min) | (Pa) | dB(A) | N.W (kg) |
| SHT-20 | 200mm | 200 | 1 | 50/60 | 250 | 2800/3300 | 25 | 245 | 65 | 7.5 |
| SHT-25 | 250mm | 250 | 1 | 50/60 | 320 | 2800/3300 | 32 | 264 | 68 | 8.5 |
| SHT-30 | 300mm | 300 | 1 | 50/60 | 420 | 2800/3300 | 42 | 278 | 70 | 11 |
| SHT-35 | 350mm | 350 | 1 | 50/60 | 520 | 2800/3300 | 52 | 292 | 72 | 13 |
| SHT-40 | 400mm | 400 | 1 | 50/60 | 620 | 2800/3300 | 62 | 306 | 74 | 15 |
| SHT-45 | 450mm | 450 | 1 | 50/60 | 720 | 2800/3300 | 72 | 320 | 76 | 17 |
| SHT-50 | 500mm | 500 | 1 | 50/60 | 820 | 2800/3300 | 82 | 334 | 78 | 19 |
| SHT-60 | 600mm | 600 | 1 | 50/60 | 1020 | 2800/3300 | 102 | 352 | 80 | 23 |
| SHT-70 | 700mm | 700 | 1 | 50/60 | 1220 | 2800/3300 | 122 | 370 | 82 | 27 |
| SHT-80 | 800mm | 800 | 1 | 50/60 | 1420 | 2800/3300 | 142 | 388 | 84 | 31 |
| SHT-90 | 900mm | 900 | 1 | 50/60 | 1620 | 2800/3300 | 162 | 406 | 86 | 35 |
| SHT-100 | 1000mm | 1000 | 1 | 50/60 | 1820 | 2800/3300 | 182 | 424 | 88 | 39 |
| SHT-120 | 1200mm | 1200 | 1 | 50/60 | 2220 | 2800/3300 | 222 | 456 | 90 | 47 |
| SHT-150 | 1500mm | 1500 | 1 | 50/60 | 2720 | 2800/3300 | 272 | 488 | 92 | 55 |
| SHT-180 | 1800mm | 1800 | 1 | 50/60 | 3220 | 2800/3300 | 322 | 520 | 94 | 63 |
| SHT-200 | 2000mm | 2000 | 1 | 50/60 | 3720 | 2800/3300 | 372 | 552 | 96 | 71 |
| SHT-250 | 2500mm | 2500 | 1 | 50/60 | 4720 | 2800/3300 | 472 | 584 | 98 | 83 |
| SHT-300 | 3000mm | 3000 | 1 | 50/60 | 5720 | 2800/3300 | 572 | 616 | 100 | 95 |
| SHT-350 | 3500mm | 3500 | 1 | 50/60 | 6720 | 2800/3300 | 672 | 648 | 102 | 107 |
| SHT-400 | 4000mm | 4000 | 1 | 50/60 | 7720 | 2800/3300 | 772 | 680 | 104 | 119 |
| SHT-450 | 4500mm | 4500 | 1 | 50/60 | 8720 | 2800/3300 | 872 | 712 | 106 | 131 |
| SHT-500 | 5000mm | 5000 | 1 | 50/60 | 9720 | 2800/3300 | 972 | 744 | 108 | 143 |
| SHT-600 | 6000mm | 6000 | 1 | 50/60 | 11720 | 2800/3300 | 1172 | 776 | 110 | 167 |
| SHT-700 | 7000mm | 7000 | 1 | 50/60 | 13720 | 2800/3300 | 1372 | 808 | 112 | 181 |
| SHT-800 | 8000mm | 8000 | 1 | 50/60 | 15720 | 2800/3300 | 1572 | 840 | 114 | 195 |
| SHT-900 | 9000mm | 9000 | 1 | 50/60 | 17720 | 2800/3300 | 1772 | 872 | 116 | 209 |
| SHT-1000 | 10000mm | 10000 | 1 | 50/60 | 19720 | 2800/3300 | 1972 | 904 | 118 | 223 |
| SHT-1200 | 12000mm | 12000 | 1 | 50/60 | 23720 | 2800/3300 | 2372 | 968 | 120 | 263 |
| SHT-1500 | 15000mm | 15000 | 1 | 50/60 | 29720 | 2800/3300 | 2972 | 1032 | 122 | 303 |
| SHT-1800 | 18000mm | 18000 | 1 | 50/60 | 35720 | 2800/3300 | 3572 | 1096 | 124 | 343 |
| SHT-2000 | 20000mm | 20000 | 1 | 50/60 | 41720 | 2800/3300 | 4172 | 1160 | 126 | 383 |
| SHT-2500 | 25000mm | 25000 | 1 | 50/60 | 51720 | 2800/3300 | 5172 | 1224 | 128 | 443 |
| SHT-3000 | 30000mm | 30000 | 1 | 50/60 | 61720 | 2800/3300 | 6172 | 1288 | 130 | 503 |
| SHT-3500 | 35000mm | 35000 | 1 | 50/60 | 71720 | 2800/3300 | 7172 | 1352 | 132 | 563 |
| SHT-4000 | 40000mm | 40000 | 1 | 50/60 | 81720 | 2800/3300 | 8172 | 1416 | 134 | 623 |
| SHT-4500 | 45000mm | 45000 | 1 | 50/60 | 91720 | 2800/3300 | 9172 | 1480 | 136 | 683 |
| SHT-5000 | 50000mm | 50000 | 1 | 50/60 | 101720 | 2800/3300 | 10172 | 1544 | 138 | 743 |
| SHT-6000 | 60000mm | 60000 | 1 | 50/60 | 121720 | 2800/3300 | 12172 | 1608 | 140 | 843 |
| SHT-7000 | 70000mm | 70000 | 1 | 50/60 | 141720 | 2800/3300 | 14172 | 1672 | 142 | 943 |
| SHT-8000 | 80000mm | 80000 | 1 | 50/60 | 161720 | 2800/3300 | 16172 | 1736 | 144 | 1043 |
| SHT-9000 | 90000mm | 90000 | 1 | 50/60 | 181720 | 2800/3300 | 18172 | 1800 | 146 | 1143 |
| SHT-10000 | 100000mm | 100000 | 1 | 50/60 | 201720 | 2800/3300 | 20172 | 1864 | 148 | 1243 |

ADDITIONAL IMAGES



Product Overview

High-Performance Industrial Ventilation

This adjustable industrial blower fan is designed for professional environments requiring reliable supply and exhaust ventilation. It features a robust metal housing with a powder-coated finish for corrosion resistance and an integrated handle for easy portability. Ideal for long-distance air movement in ship building, municipal engineering, and chemical facilities, it combines high wind pressure with a stable, safe design.

Design & Portability

Design Features

Adjustable Stand, Built-in Handle, Portable Design, Powder-Coated Finish, One-Piece Safety Switch

Safety & Construction

Safety Protections

- Protective grill to prevent blade contact
- Thermal overload motor protection
- Durable metal housing
- Stable capacity design

Performance Range

Key Performance Metrics

200 mm

Minimum Diameter

600 mm

Maximum Diameter

3300 r/min

Max Rotation Speed

Technical Specifications

Technical Data Sheet

| Model | Size (mm) | Power (W) | Capacity (m ³ /min) | Static Pressure (Pa) | Noise (dB(A)) |
|--------|-----------|-----------|--------------------------------|----------------------|---------------|
| SHT-20 | 200 | 230 | 25 | 245 | 60 |
| SHT-25 | 250 | 320 | 43 | 294 | 68 |
| SHT-30 | 300 | 520 | 65 | 370 | 78 |
| SHT-35 | 350 | 750 | 82 | 598 | 80 |
| SHT-40 | 400 | 1100 | 96 | 700 | 80 |
| SHT-50 | 500 | 2000 | 200 | 1050 | 88 |
| SHT-60 | 600 | 2200 | 240 | 1100 | 92 |

Applications

Primary Applications

- Communication cable maintenance
- Ship building and repairing
- Municipal underground engineering
- Chemical industrial factories
- Large capacity tank containers

Electrical Requirements

Available Voltages

110V • 220V • 380V