

Aluminum Camlock Hose Coupling Type D

This aluminum camlock coupling, Type D, facilitates rapid connection and disconnection of hoses and pipes. Constructed from aluminum, it offers corrosion resistance and lightweight handling for various applications.



ADDITIONAL IMAGES



Overview

Aluminum Camlock Coupling Type D

This Type D aluminum camlock coupling is designed for rapid, tool-free connection and disconnection of hoses and pipes. Engineered for efficiency, it offers excellent abrasion resistance, a lightweight profile, and cost-effective performance for fluid, powder, and pellet transfer. It ensures a reliable, leak-proof seal, making it an essential component for industrial, irrigation, and chemical handling applications.

Technical Specifications

Available Sizes	1/2 inch to 8 inches
Body Material	Aluminum
Pins, Rings, and Clips Material	Carbon steel plated, Stainless steel
Handle Material	Brass, Stainless steel
Seal Options	NBR, BUNA, EPDM, VITON

Performance Metrics

Maximum Working Pressure

250 psi
Max Pressure

Working Temperature

-150°F to +250°F

Standards and Compliance

Manufacturing Standards

A-A-59326 • MIL-C-27487 • DIN 2828

Logistics

Production Lead Time	30 days
Shipping Port	FOB Qingdao