


Automated Poly Bag Uncuffing and Sealing Machine

Poly bag uncuffing and sealing machine automates bag in box packaging processes. It uncuffs the bag from carton flaps, stretches and vacuumizes it before sealing and flattening.



ADDITIONAL IMAGES



Product Overview

Automated Poly Bag Uncuffing and Sealing

This automated poly bag uncuffer and top sealer is engineered to streamline the heat-sealing process for bag-in-box packaging applications. The system automatically uncuffs bags from carton flaps, stretches the top, applies a light vacuum to prevent ballooning, and seals the bag before flattening it within the carton. Designed to reduce labor and material costs, it offers a highly efficient, simple-to-operate solution for high-volume packaging lines.

Performance

Capacity

3 cartons/min

Min Capacity

5 cartons/min

Max Capacity

Technical Specifications

Film Width	460 mm
Max Film Width	840 mm
Power Supply	3 phases, 7 kW
Compressed Air Pressure	6 bar
Air Consumption	100 NL/min

Compatibility

Applicable Carton Dimensions

Dimension	Range (mm)
Length	250-550
Width	200-400
Height	150-400

Machine Dimensions

Overall Dimensions (L x W x H)	3322 x 2177 x 2350 mm
--------------------------------	-----------------------

Features

Core Functions	Uncuffing, Heat-sealing, Vacuumizing, Carton Flattening, Adjustable
----------------	---