

# BLDC Motor Driver 10-50V 15A

This brushless DC motor driver is designed for medium-power brushless motors. It is suitable for driving any three-phase brushless DC motor, Hall or no Hall sensor, with peak current below 15A and power supply voltage between DC10V~50V.



## Overview

### High-Performance Brushless DC Motor Driver

The NSPBLDS4815 is a high-tech brushless DC motor driver designed for medium-power applications in electrical automation, medical equipment, and food packaging. It features a large-scale integrated circuit design that ensures superior anti-interference performance and fast response times. Compatible with both sensed and sensorless three-phase BLDC motors, this driver offers versatile control options and robust protection features for reliable industrial operation.

## Performance Specifications

### Electrical Characteristics

Parameter	Value
Power Supply	DC10V-50V
Rated Current	15A
Rated Power	Max 720W
Insulation Resistance	>500M $\Omega$
Insulation Strength	0.5KV, 1min

### Key Metrics

<b>50 V</b> Max Voltage	<b>15 A</b> Rated Current	<b>10000 rpm</b> Max Speed
----------------------------	------------------------------	-------------------------------

## Operating Environment

### Conditions

- Operating Temperature: 0°C to +50°C
- Storage Temperature: -20°C to +65°C
- Humidity: <80%RH (no condensation)
- Cooling: Natural or forced air cooling

## Features

### Safety Functions

Over Current • Over Voltage • Under Voltage • Motor Block Protection

### Control Features

Hall Sensor Support, Sensorless Support, 0-5V Analog Control, PWM Control (10Hz-500Hz), Directional Control, Enable/Disable Input

## Dimensions

Physical Size	118 x 77 x 33.5 mm
Weight	0.3 kg