

# Brass Camlock Coupling with Viton Gaskets

This brass camlock coupling allows for quick and reliable connection of hoses and pipes. Viton gaskets provide a secure seal and compatibility with various fluids.



## ADDITIONAL IMAGES



## Product Overview

### High-Performance Brass Camlock Couplings

These brass camlock couplings are designed for efficient, tool-free hose and pipe connections in industrial fluid transfer systems. Featuring durable brass construction and high-performance Viton gaskets, they offer excellent corrosion resistance and superior sealing capabilities. Ideal for low-pressure suction or discharge applications, these couplings provide a reliable solution for handling oils, coolants, and water in demanding environments.

## Technical Specifications

### Available Sizes

- 1/2"
- 3/4"
- 1"
- 1-1/4"
- 1-1/2"
- 2"
- 2-1/2"
- 3"
- 4"
- 5"
- 6"

<b>Body Material</b>	Brass
<b>Gasket Material</b>	Viton
<b>Thread Options</b>	NPT, BSPP, BSPT

## Performance Metrics

### Key Performance Metrics

**250 psi**

Max Working Pressure

**232 °C**

Max Temperature

**-101 °C**

Min Temperature

## Compatibility & Standards

### Available Coupling Types

Type A • Type B • Type C • Type D • Type E • Type F • Type DC • Type DP

### Standards Compliance

A-A-59326, MIL-C-27487, DIN 2828, DIN 14420-7

## Usage Guidelines

### Important Usage Notes

- Not suitable for compressed air applications
- Not suitable for steam transfer
- Not suitable for liquid gases
- Ideal for oils, coolants, and water