



## Performance Data

Model	Material	Capacity (m <sup>3</sup> /h)	Head (m)	Max Power (kW)	Speed (rpm)
40PV	Metal/Rubber	7.2-39.6	3.9-27.4	15	1000-2200
65QV	Metal/Rubber	19.08-102.6	5-31.1	30	700-1500
100QV	Metal/Rubber	41.5-259.2	5.1-37.2	70	500-1200
150SV	Metal/Rubber	115.2-576	6.7-35.7	110	500-1000
200SV	Metal/Rubber	180-734.4	7.1-28.2	110	400-850
250TV	Metal/Rubber	363-1188	7-36	200	400-750
300TV	Metal/Rubber	385-1492	7.8-55	250	400-700

Performance ranges for different models, from 40PV to 300TV, covering capacity, head, and power requirements.

### Model Performance Specifications

Model	Capacity (m <sup>3</sup> /h)	Head (m)	Max Power (kW)	Speed (rpm)
40PV	7.2-39.6	3.9-27.4	15	1000-2200
65QV	19.08-102.6	5-31.1	30	700-1500
100QV	41.5-259.2	5.1-37.2	70	500-1200
150SV	115.2-576	6.7-35.7	110	500-1000
200SV	180-734.4	7.1-28.2	110	400-850
250TV	363-1188	7-36	200	400-750
300TV	385-1492	7.8-55	250	400-700