


# Category 5e Unshielded Twisted Pair Cable

This high-performance communication cable exceeds ANSI/TIA/EIA-568B.2 Category 5e standards. Its optimized outer diameter minimizes twisting and tangling during installation, making it suitable for horizontal subsystem connections.

- ▶ 标准：优于现行的ANSI/TIA/EIA-568B.2五类线缆标准要求。
- ▶ 功能及优点：传输速率低，连接稳定一致，具有优异的电磁干扰性，使传输信号的误码率明显降低。合适的外径尺寸，减少安装中的扭曲或打结。
- ▶ 产品类别：适用于水平子系统的连接。



产品编号	产品名称	包装
TXL102	超五类4对非屏蔽双绞线	305米/箱

## Overview

### High-Performance Category 5e Connectivity

This Category 5e 4-pair unshielded twisted pair cable is engineered to exceed ANSI/TIA/EIA-568B.2 standards, ensuring reliable performance for modern networking environments. Designed with low transmission delay and superior insulation consistency, it significantly reduces signal error rates for stable data transmission. The optimized outer diameter facilitates easier installation by minimizing tangling, making it an ideal choice for horizontal subsystem connections.

## Technical Specifications

Product Code	TXL102
Cable Type	Category 5e 4-pair Unshielded Twisted Pair (UTP)
Standards Compliance	ANSI/TIA/EIA-568B.2

## Packaging & Logistics

Packaging Length	305 meters/box
------------------	----------------

## Performance Features

### Key Features

- Low transmission delay
- Consistent insulation
- High electromagnetic interference (EMI) resistance
- Reduced transmission signal error rates
- Optimized outer diameter for easy installation

## Applications

Primary Application	Horizontal subsystem connections
---------------------	----------------------------------