

CCTV Indoor Pan Scanner

This indoor pan scanner is designed for CCTV systems, providing continuous horizontal rotation. It is compatible with 24V, 110V, and 220V AC power, and suitable for 24-hour monitoring.



Product Overview

Professional Indoor Pan Scanner

This indoor pan scanner is engineered for reliable, 24-hour surveillance operations, featuring smooth, circular motion and advanced magnetic induction control. Designed for longevity, the unit incorporates needle roller bearings and ball bearings to significantly reduce wear and extend operational lifespan. Its robust, integrally formed structure prevents deformation, making it a dependable choice for indoor security environments requiring consistent, wide-angle monitoring.

Performance Specifications

Pan Speed

6 °/sec

60Hz

5 °/sec

50Hz

Pan Travel	355 °
Motor Torque	40 Kgf-cm
Maximum Load	20 Kgs

Electrical & Environmental

Power Supply Options

- AC 24V ±5% (60/50Hz)
- AC 110V ±10% (60/50Hz)
- AC 220V ±10% (60/50Hz)

Power Consumption	2 W
Operating Temperature	-5°C to +65°C
Operating Humidity	35% ~ 95% RH

Physical Dimensions

Unit Dimensions	125mm (W) x 119mm (Ø)
Unit Weight	1.13 kg
Scanner Case Dimensions	125mm (L) x 125mm (W) x 130mm (H)

Logistics & Compliance

Packaging Details

Metric	Value
Quantity per Package	12 pieces
Net Weight / Gross Weight	12.5 kg / 14.7 kg
Dimensions	40cm (L) x 29cm (W) x 30cm (H)

Certifications	CE, RoHS
Warranty	2 years