

Commercial Audio Amplifier with Multiple Inputs

This commercial audio amplifier is designed for professional audio systems. It offers multiple input options such as MP3, BGM, VOD, DVD, and Bluetooth connectivity.



ADDITIONAL IMAGES



Overview

Professional Commercial Audio Amplifier

This high-performance commercial audio amplifier is designed for professional sound reinforcement, featuring 200W+200W RMS output power and a 32-bit DSP reverberation system. It offers extensive connectivity with multiple AV inputs, five microphone jacks, and dedicated tone controls for both music and vocals. Built for reliability, the unit includes comprehensive protection circuits against short circuits, thermal overload, and power transients, making it an ideal solution for commercial audio installations.

Performance Metrics

RMS Output Power

200 W

Per Channel (8 ohm)

Music Frequency Response: 20Hz-20KHz (± 1.5 dB)

Signal to Noise Ratio (Music): 80 dB

Connectivity & Inputs

Microphone Channels	5
Music Input Channels	4
Input Impedance	47K ohm

Control & Features

Key Features	32Bit DSP, LCD Display, Remote Control, Active Subwoofer Jack, Auto Input Detection
Tone Control Range	± 10 dB (10KHz)

Physical & Technical

Power Requirements	AC 200V-240V, 50-60Hz
Dimensions	430 x 400 x 145 mm
Net Weight	14 kg
Cooling	Variable speed fan