

Compact Hydraulic Excavator

This hydraulic excavator has an operating weight of 13,008 lb and a bucket capacity ranging from 0.13 to 0.36 yd³. It offers a maximum digging depth of 12' 9" and complies with EU Stage IIIA/ EPA Tier 3 emissions standards.



Overview

Compact Hydraulic Excavator

This compact hydraulic excavator is engineered for high performance in demanding construction environments, offering a balance of power and precision. Designed with operator comfort and safety in mind, it features a robust cabin with excellent visibility and intuitive controls. Its efficient hydraulic system and durable construction ensure reliability for various digging, trenching, and material handling tasks.

Key Performance Metrics

13008 lb

Operating Weight

46 hp

Net Power

12.75 ft

Max Digging Depth

Performance & Technical

Technical Specifications

Specification	Value
Engine Power Speed	2,100 rpm
Bucket Capacity Range	0.13 - 0.36 yd ³
Emission Standard	Tier 3 / EU Stage IIIA

Operator Safety and Comfort

Cabin Features

- ROPS / FOPS certified cabin
- Soundproofed environment with air conditioning
- 360° visibility
- Ergonomic instrument placement
- Easy-to-clean durable floor mats

Hydraulic Control Systems

Pattern Control Changer • Hammer/Shear Hydraulics • Boom Anti-Drift Function • ISO/BHL Pattern Switchable

Reliability

Build Quality	Reinforced D-shaped frame designed to protect against damage and external shock.
Hydraulic System	Proven and reliable negative flow hydraulic system.

Easy to Maintain

Maintenance Accessibility

- Ground-level access to air, fuel, and hydraulic filters
- Easy engine compartment access
- LCD display with integrated maintenance information