

# Copper Cable Lugs

These cable lugs are designed for connecting copper conductors in power cables to electronic equipment. They are constructed from 99.99% pure copper tube T2 and feature a tin coating.



## ADDITIONAL IMAGES



## Product Overview

### High-Performance Copper Cable Lugs

These cable lugs are engineered for the reliable connection of copper conductors in power cable systems and electronic equipment. Manufactured from 99.99% pure T2 copper tube and finished with a durable tin coating, they ensure excellent electrical conductivity and superior corrosion resistance. Designed to perform in demanding environments, these lugs support a wide range of conductor cross-sections and are built for long-term operational stability.

## Technical Specifications

Conductor Cross-Section	1.5 - 400 mm <sup>2</sup>
Material	99.99% Pure T2 Copper
Surface Finish	Tin-plated
Operating Temperature Range	-55°C to 150°C
Certifications & Standards	RoHS, ISO 9001:2015, IATF 16949

## Dimensional Data

### Standard Dimension Reference

Item No.	E	C	A	L
GPH1.5-3	3.2	3.3	1.8	15.5
GPH2.5-4	4.3	4.2	2.2	17.1
GPH6-5	5.3	6.5	3.5	28.2
GPH16-6	6.4	8.5	5.5	33.5
GPH50-10	10.5	14	10	51.2
GPH120-12	13.2	19.5	15	68
GPH240-16	17	26.2	21	89
GPH400-20	21	33.7	27.5	119