

Copper Crimp Connector Eyelet Terminal

These copper crimp connector eyelet terminals facilitate secure and reliable electrical connections. Constructed from high-conductivity copper, they ensure optimal conductivity and corrosion resistance for long-lasting performance.



ADDITIONAL IMAGES



Product Overview

High-Performance Copper Crimp Terminals

These high-conductivity copper cable lugs are engineered for secure and reliable electrical connections across a wide range of industrial applications. Manufactured from 99.9% pure T2 copper and tin-coated for superior corrosion resistance, they are designed to perform in demanding environments with a wide operating temperature range of -55°C to 150°C. They meet rigorous international safety and quality standards, making them an ideal choice for power cable termination in electronic equipment and heavy-duty electrical systems.

Technical Specifications

Working Temperature

-55 °C Min Temperature	150 °C Max Temperature
----------------------------------	----------------------------------

Material	High Conductivity Copper (99.9% Purity)
Coating	Tin-plated (Acid washing)
Certifications	CE, UL, JIS, DIN, AWG

Dimensions & Sizing

Terminal Dimensions

Item No	E	D	d	W	L
8#10	5.1	7.1	4.8	11.8	33.3
8*1/4	6.8	7.1	4.8	11.8	33.3
8*5/16	8.3	7.1	4.8	11.8	33.3
6#10	5.1	8.1	5.9	11.8	37.3
6*1/4	6.8	8.1	5.9	13.7	37.3
4*1/4	6.8	9.5	7.3	13.8	38.9
2*1/4	6.8	11.1	8.5	16.5	41.1
1*1/4	6.8	11.7	9.1	16.4	43.6
1/0 1/4	6.8	13	10.4	18.4	46.8
2/0 1/4	6.8	14.2	11.7	21	52.4
3/0 5/16	8.3	15.7	13	23.1	55.9
4/0 1/2	13.1	17.2	14.2	25.8	60.5