

Digital Television Broadcast Receiver

This digital television broadcast receiver is engineered to decode and display digital television broadcasts. It features ANT-IN, USB, HDMI, and AV OUT ports for versatile connectivity.



ADDITIONAL IMAGES



Overview

High-Definition ISDB-T Digital Receiver

This versatile digital television broadcast receiver is fully compliant with ISDB-T standards, providing reliable HD and SD signal decoding. It features advanced multimedia capabilities including USB 2.0 PVR functionality for recording and playback, as well as support for various video and audio formats. Designed for ease of use, it includes comprehensive channel editing tools and a user-friendly electronic program guide (EPG) for an enhanced viewing experience.

Core Capabilities

Supported Resolutions

- 480i
- 480p
- 576i
- 576p
- 720p
- 1080i

Standards Compliance

ISDB-T, MPEG-2, MPEG-4, H.264

Connectivity & Media

Available Ports

HDMI • USB 2.0 • Mini AV • RF Loop Out

Media Playback Features

- PVR (Personal Video Recording)
- MP3 Audio Playback
- JPG Photo Playback
- Teletext & Subtitle Support

Technical Specifications

Power Requirements

5 V

Input Voltage

8 W

Max Consumption

0.5 W

Standby Power

Frequency Range

VHF 170-216MHz / UHF 470-858MHz

Dimensions

100 x 100 x 23 mm

Logistics

Container Loading Capacity

| Container Type | Quantity |
|----------------|----------|
| 20' GP | 16000 |
| 40' GP | 32000 |
| 40' HQ | 36000 |