

# Double Action Tact Switch with Double Push Button

This double action tact switch features a double push button design. It is suitable for applications requiring reliable and precise actuation.



## ADDITIONAL IMAGES



## Product Overview

### Industrial Double-Action Tact Switch

This double-action tact switch combines a dual push-button interface with an integrated central pilot light, designed for precise control in demanding industrial environments. Constructed with high-grade anti-flame plastic and professional-grade silver alloy contacts, it offers high resistance to electrical erosion and long-term reliability. The unit is ideal for control circuits in distribution cabinets, power stations, and communication networks.

## Electrical Specifications



**Specializing in production of buttons and indicators since 1997**

The switch is rated for AC-15A applications with versatile voltage compatibility.

Rated Insulation Voltage	AC 600V (50/60Hz)
Conventional Heating Current	10 A
Insulation Resistance	e50M©
Contact Resistance	d25m©
Withstand Voltage	AC 2.5 kV/min

## Technical Performance

### Mechanical Life

**1000000 cycles**  
Pushbutton

**500000 cycles**  
Selector Switch

### Electrical Life

**5000000 cycles**  
Pushbutton

**250000 cycles**  
Selector Switch

## Physical and Environmental




**Illuminated double-headed  
Push button  
with integral LED**  
 1 flush green marked I  
 1 flush red marked O  
 1 central pilot light

XDL21-EBW8365 IP40

N/O+N/C  
220~240V




 Green  
 Yellow  
 Red



Dimensional and contact configuration details.

### Ingress Protection

IP40

### Mounting Type

M22

### Dimensions

80mm x 30mm

## Certifications

### Standards and Compliance

CE, IEC 60947-5-1, GB/T 14048.1, ISO 9001, RoHS