

Double Hole Copper Cable Lug

These copper compression lugs are designed for secure and reliable cable terminations, ideal for double-hole cable connections. They ensure optimal conductivity and mechanical strength.



ADDITIONAL IMAGES



Product Overview

High-Performance Copper Cable Lugs

These double-hole copper compression lugs are engineered for secure and reliable cable terminations in power distribution and electronic equipment. Manufactured from 99.99% pure T2 copper with a durable tin-plated surface, they ensure excellent conductivity and corrosion resistance. Designed to operate effectively in extreme temperatures ranging from -55°C to 150°C, these lugs meet rigorous international safety and quality standards.

Technical Specifications

Operating Temperature Range

-55 °C

Min Temperature

150 °C

Max Temperature

Material	99.99% Pure Copper (T2)
Surface Treatment	Tin-plated
Compatible Conductor Range	1.25 - 5.5 mm ²

Certifications & Standards

Safety Certifications

CE • UL

Compliance Standards	JIS, DIN, AWG
----------------------	---------------

Dimensional Data

Standard Dimensions

Item No	OD	ID	F	B	L	T
TPIN1.25	3.4	1.7	2	4.5	16.3	0.75
TPIN2	4	2.3	2	4.8	17	0.75
TPIN5.5	5.6	3.5	2.7	6.8	20.5	1