

Double-Hole Copper Tube Terminal Lug

These double-hole tube terminal lugs are designed for connecting copper conductors to power cables and electronic equipment. They are made from 99.99% pure copper tube T2 and feature a tin coating for enhanced conductivity and corrosion resistance.



ADDITIONAL IMAGES



Product Overview

CL Double-Hole Tube Terminal Lugs

These CL-TYPE 2-hole cable lugs are engineered for the reliable connection of copper conductors in power cabling and electronic equipment. Manufactured from high-purity 99.99% T2 copper tubing and finished with a protective tin coating, they offer superior conductivity and corrosion resistance. Designed to withstand demanding environments, they operate effectively within a temperature range of -55°C to 150°C.

Technical Specifications

Operating Temperature

-55 °C

Min Temperature

150 °C

Max Temperature

Material	99.99% Pure T2 Copper
Finish	Tin Coated
Conductor Section Range	14-500 mm ²
Compliance & Standards	RoHS, ISO 9001:2015, IATF 16949, IRIS

Dimensional Data

Standard Dimensions

Item No.	￼	OD	ID	D	B	L
CL14-2H-6	6.4	8.8	5.8	13	28.5	117.5
CL22-2H-8	8.4	11.3	7.7	16	28.5	119.2
CL38-2H-10	10.5	12.4	9.8	18.3	31.7	120
CL60-2H-10	10.5	14	11	20.5	40	130
CL100-2H-12	13	18	14	26	42	132
CL200-2H-12	13	26	20	36	50	150
CL500-2H-12	13	40	31	56	60	180