


# Double-Sided LED Sign

This double-sided LED sign is designed for versatile display applications. It features front service access for easy maintenance and is available in various pixel pitches.



## ADDITIONAL IMAGES



## Overview

### High-Performance Double-Sided Outdoor LED Display

This P10 outdoor LED screen features a double-faced design, making it an ideal freestanding solution for high-visibility advertising. Engineered for durability and ease of use, it supports front-service access for simplified maintenance in various outdoor environments. With high brightness levels and a wide viewing angle, it ensures your content remains clear and impactful even in direct sunlight.

## Key Performance Metrics

### Performance Highlights

**7500 cd/m<sup>2</sup>**  
Brightness

**1000 Hz**  
Refresh Rate

**100000 Hours**  
Life Span

## Display Specifications

Pixel Pitch	10 mm
Physical Density	10000 pixels/m <sup>2</sup>
LED Arrangement	DIP346
Viewing Angle (H/V)	120° / 60°

## Module & Cabinet Details

### Module Specifications

Feature	Value
Module Dimension	160x160 mm
Module Resolution	16x16 pixels
Cabinet Dimension	1280x480 mm
Cabinet Resolution	128x48 pixels

Cabinet Weight	70 kg/m <sup>2</sup>
----------------	----------------------

## Power & Environment

### Power Consumption

Type	Value
Max Power Consumption	700w/m <sup>2</sup>
Average Power Consumption	300w/m <sup>2</sup>

### Ingress Protection

IP65

Operating Temperature	-10° to 45°C
-----------------------	--------------

## Connectivity

Supported Signal Inputs	Composite, S-Video, Component, VGA, DVI, HDMI, SDI, HD SDI
Scan Method	1/4