

Dump Tractor

This dump tractor is a robust vehicle designed for heavy-duty hauling and dumping. Its rugged construction and off-road capabilities make it suitable for demanding work environments.



ADDITIONAL IMAGES

Item	Specifications	Remarks
Cabin	Type 2042, bag hood, single seat one	
Engine	YC21050(M) or S2.1105ABN(8hp)	140-dash housing
Gearbox	140+130 gearbox	4T/5T
Frame	Revised with 2 layers of steel plate, with height of 200mm	Thickness 6+4mm, material Q235L
Axle	Loading: 4T/5T, air brake	
Hydraulic cylinder	400-130, 4T/5T-150	Two cylinder or single mounted, cylinder optional
Steering gear	Type 140	Power steering optional
Clutch	Type 140	
Brake	Air brake	
Pushing brake	Electric brake	
Lamp type	Type 121 improved	
Battery	12V, 80Ah, two	
Loading space	2.8m x 1.8m x 0.7m	To be extended as per requirements.
Tire	From 700-16-2, size: 8.25-16-2	
Overall size LxWxH	5000mm x 2000mm x 2300mm	
Wheelbase	3200 mm	
REAR track	1540/1580	



Overview

Robust Hauling Performance

This dump tractor is engineered for heavy-duty hauling and reliable operation in demanding environments. Featuring a reinforced frame and high-capacity dump bed, it is built to handle medium and short-distance transportation tasks in both urban and rural settings. Its rugged construction, combined with flexible steering and excellent grade-ability, ensures efficient material handling and consistent performance.

Performance & Powertrain

Engine Options	60hp, 68hp
Gearbox Configuration	140+130 gearbox ((5+1)x4)
Clutch Type	Type 140
Steering	Type 140 (Power steering optional)

Chassis & Build

Frame Construction	Revised with 2 layers of steel plate (thickness 6+4mm, height 200mm)
Wheelbase	3200 mm
Axle Loading Capacity	4T/5T

Dimensions & Capacity

Overall Dimensions (LxWxH)	5000mm x 2000mm x 2300mm
Loading Space	2.8m x 1.8m x 0.7m
Track Width (FRT/RR)	1540mm / 1580mm

Safety & Electrical

Braking System	Air brake, Exhaust brake, Vacuum-assisted optional
Battery System	12V 80Ah (x2)

Tires

Tire Specifications

Position	Size
Front	700-16x2
Rear	8.25-16x2