

# Enterprise Network Computer Cable

This computer cable is designed for connections within electronic computer networks and control systems. It is compliant with enterprise standards and suitable for fixed installation in a range of ambient temperatures.

**计算机电缆**

本产品适用于电子计算机网络及系统控制系统的连接。

- **电缆执行标准:**  
企标标准。
- **电缆使用特性:**  
1) 额定电压(U<sub>0</sub>/U)为450/750V;  
2) 导体最高工作温度为90℃;  
3) 电缆可在任何敷设, 可在-50℃条件下长期连续使用, 安装敷设时环境温度不低于0℃;  
4) 铠装屏蔽电缆最小弯曲半径为10倍电缆外径, 其它屏蔽电缆最小弯曲半径为5倍电缆外径。

电缆型号、名称: 见表14-1

型号(Model)	名称(Name)
DJYVP	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机电缆 Computer cable with PE insulation & PVC sheath, general twisted shielding & PVC sheath
DJYVP1	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机(双导线)计算机电缆 Computer cable with PE insulation & PVC sheath, twisted shielded shielding & PVC sheath
DJYVP2	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机(四导线)计算机电缆 Computer cable with PE insulation & PVC sheath, twisted shielded shielding & PVC sheath
DJYVP3	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机(四导线)计算机电缆 Computer cable with PE insulation & PVC sheath, twisted shielded shielding & PVC sheath
DJYVP4	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机(四导线)计算机电缆 Computer cable with PE insulation & PVC sheath, twisted shielded shielding & PVC sheath
DJYVP5	聚乙烯绝缘铜芯聚氯乙烯护套阻燃型计算机(四导线)计算机电缆 Computer cable with PE insulation & PVC sheath, twisted shielded shielding & PVC sheath