

Female Cam Lock Coupling - Stainless Steel Type DC

This stainless steel camlock fitting can be used with salt water, water waste, many chemicals, hydraulic oil, and coolants. The quick coupling features excellent corrosion resistance, high temperature capability, and a long life expectancy.



ADDITIONAL IMAGES



Product Overview

High-Performance Stainless Steel Camlock Coupling

This Type DC female camlock coupling, or dust cap, is engineered for quick and secure connections in demanding industrial, agricultural, and chemical transfer applications. Constructed from high-grade stainless steel, it offers exceptional corrosion resistance, high-temperature tolerance, and a long service life. Its lever-actuated cam locking mechanism ensures a tight, leak-proof seal, making it an essential component for efficient fluid handling systems.

Technical Specifications

Available Sizes

- 1/2"
- 3/4"
- 1"
- 1-1/2"
- 2"
- 2-1/2"
- 3"
- 4"
- 6"
- 8"

Working Pressure Ratings

Size Range	Pressure (PSI)	Pressure (bar)
3/4" - 2"	250	17.6
2-1/2"	225	15.8
3" - 4"	200	14.8
6"	150	10.5

Working Temperature

-150 F

Min Temperature

500 F

Max Temperature

Compliance Standards

A-A-59326 • MIL-C-27487 • DIN 2828

Material Options

Stainless Steel 304, Stainless Steel 316

Construction Details

Seal Material Options	NBR, BUNA, EPDM, VITON
Handle Material	Brass or Stainless Steel
Pins, Rings, and Clips Material	Carbon steel plated or stainless steel
Manufacturing Method	Precision casting or forged