

Female Threaded Stainless Steel Swing Check Valve

This stainless steel swing check valve prevents backflow in pipelines. It has female threaded ends for easy installation.



Product Overview

Industrial Swing Check Valve

The Female Threaded Stainless Steel Swing Check Valve is engineered for reliable backflow prevention in demanding industrial pipeline systems. Utilizing investment casting and premium stainless steel materials, this valve ensures structural integrity and excellent corrosion resistance. Its versatile design supports a wide temperature range and diverse media, making it an ideal solution for consistent, one-way flow control.

Technical Specifications

Working Pressure

1000 Psi

Working Pressure

64 PN

Pressure Rating

Operating Temperature

-60°F to 450°F (-20°C to 232°C)

Applicable Media

WOG, Nitric Acid, Acetic Acid

Manufacturing Standards

Compliance & Standards

Standard Type	Reference
Design & Making	ANSI B 16.34
Inspection & Test	API 589
Structure Length	GB/T 15188.3-94

Available Materials

- ASTM A351-CF8M (316)
- ASTM A351-CF8 (304)
- ASTM A216-WCB
- DIN 1.4308
- DIN 1.4408

Installation

Thread Standards

G • BSPT • NPT • BSP • DIN259/2999 • ISO7/1-1982