

# Hot-Dip Galvanized Suspended Platform for Elevated Work

This suspended platform is constructed from hot-dip galvanized steel and aluminum. It is designed for various elevated work applications, including window cleaning and facade maintenance.



## Overview

### Professional Suspended Access Solutions

This hot-dip galvanized suspended platform is engineered for high-altitude operations, including facade maintenance, window cleaning, and construction. Available in ZLP630 and ZLP800 configurations, these systems feature robust steel and aluminum construction for superior corrosion resistance and durability. The modular design allows for rapid assembly and customization, while integrated safety mechanisms ensure operator security on the job site.

## Key Metrics

### Performance Specifications

**630 kg**

Rated Load (ZLP630)

**800 kg**

Rated Load (ZLP800)

**9.5 m/min**

Lifting Speed (ZLP630)

**8.5 m/min**

Lifting Speed (ZLP800)

## Technical Details

### Model Comparison

Specification	ZLP630	ZLP800
Platform Size (L*W*H)	(2000*3)*690*1180mm	(2500*3)*690*1180mm
Hoist Type	LTD63	LTD80

## Suspension System

### Suspension Mechanism

- Front beam extension: 1.1m - 1.5m
- Height adjustment: 1.45m - 1.75m

## Certifications

### Compliance & Standards

CE, ISO 9001, CNAS, CQC