

HRC Industrial Fuse

This HRC fuse is lightweight and small in size, offering a high breaking capacity. It is designed for reliable quality and performance in a variety of industrial applications.



ADDITIONAL IMAGES



Product Overview

Industrial HRC Fuse Links

These industrial HRC (High Rupturing Capacity) fuse links are designed for robust overcurrent protection in demanding electrical environments. Featuring a durable porcelain body with copper clamps and blades, they offer reliable performance and high breaking capacity. The square-bodied design includes a double indicator system, allowing for easy circuit monitoring and maintenance in distribution boxes and grid applications.

Technical Specifications

Standards Compliance

IEC60269-2-1 • VDE0636

Rated Voltage	500 VAC / 250 VDC
Operating Frequency	45-62 Hz
Available Sizes	NH00, NH0, NH1, NH2, NH3, NH4

Materials & Construction

Materials

- Porcelain body
- Copper clamp
- Copper blades

Performance Metrics

Available Current Ratings

- 2
- 4
- 6
- 10
- 16
- 20
- 25
- 32
- 35
- 40
- 50
- 63
- 80
- 100
- 125
- 160
- 200
- 224
- 315
- 350
- 400
- 630
- 800
- 1000
- 1250

Applications

Typical Use Cases

Distribution Boxes, Disconnectors, State Grid