



## Technical Specifications

### Model Dimensions & Ratings

| Model | Inner Diameter (mm) | Outer Diameter (mm) | Width (mm) | Weight (kg) |
|-------|---------------------|---------------------|------------|-------------|
| 604   | 4                   | 12                  | 4          | 0.002       |
| 605   | 5                   | 14                  | 5          | 0.0035      |
| 606   | 6                   | 17                  | 6          | 0.006       |
| 607   | 7                   | 19                  | 6          | 0.008       |
| 608   | 8                   | 22                  | 7          | 0.012       |
| 609   | 9                   | 24                  | 7          | 0.014       |
| 6000  | 10                  | 26                  | 8          | 0.019       |
| 6001  | 12                  | 28                  | 8          | 0.021       |
| 6002  | 15                  | 32                  | 9          | 0.03        |
| 6003  | 17                  | 35                  | 10         | 0.039       |
| 6004  | 20                  | 42                  | 12         | 0.069       |
| 6005  | 25                  | 47                  | 12         | 0.08        |
| 6006  | 30                  | 55                  | 13         | 0.116       |
| 6007  | 35                  | 62                  | 14         | 0.155       |
| 6008  | 40                  | 63                  | 15         | 0.185       |
| 6009  | 45                  | 75                  | 16         | 0.231       |
| 6010  | 50                  | 80                  | 16         | 0.25        |
| 6011  | 55                  | 90                  | 18         | 0.362       |
| 6012  | 60                  | 95                  | 18         | 0.385       |
| 6013  | 65                  | 100                 | 18         | 0.44        |
| 6014  | 70                  | 110                 | 20         | 0.6         |
| 6015  | 75                  | 115                 | 20         | 0.64        |
| 6016  | 80                  | 125                 | 22         | 0.854       |
| 6017  | 85                  | 130                 | 22         | 0.89        |
| 6018  | 90                  | 140                 | 24         | 1.02        |

## Performance Metrics

### Load Rating Range

**0.97 KN**

Min Dynamic Load

**58 KN**

Max Dynamic Load

### Speed Range

4000 to 43000 r/min