


Indoor LED Advertising Display

This indoor LED advertising display is available in multiple pixel pitches, including P2.5, P3, P4, P5, P5.3, and P6. It is designed for displaying high-resolution images and videos in commercial settings.



ADDITIONAL IMAGES



Product Overview

Professional Indoor LED Advertising Display

This all-in-one indoor LED advertising display offers a high-impact solution for retail environments, transport hubs, and commercial spaces. Featuring a sleek aluminum alloy frame with tempered glass protection, it combines durability with a modern aesthetic. The unit is designed for mobility and ease of use, supporting diverse content inputs and remote management to ensure your promotional messaging is always dynamic and engaging.

Display Performance

Pixel Pitch	5mm
Brightness	2000 cd/sqm
Refresh Rate	1200 Hz
Best Viewing Distance	2m - 100m

Technical Specifications

Protection Rating	IP43
Display Size (with base)	1040mm x 2200mm x 100mm
Weight	190 KG
Max Power Consumption	2000 W

Connectivity & Compatibility

Communication Methods

- Wifi
- U-disk
- 3G
- SD card
- Network cable

Supported Signal Inputs

HDMI, VGA, DVI, SDI, AV, S-Video, RGBHV, CVBS

Key Features

Performance Highlights

100000 hours

Lifespan

10000 hours

MTBF

Safety Protections

Overload protection, Low-voltage protection, Lightning protection, Leakage protection