

Indoor Omni Antenna

This indoor omni antenna is designed for communication product applications. It provides omnidirectional coverage, ensuring reliable signal reception and transmission within indoor environments.



Product Overview

High-Performance Indoor Omni Antenna

This omnidirectional indoor antenna is engineered to provide reliable signal coverage and consistent network performance across a broad frequency range. Designed for versatility, it supports multiple frequency bands from 806 MHz up to 2700 MHz, making it suitable for various wireless communication applications. Its robust construction ensures stable operation in challenging environments, while the compact form factor allows for efficient installation.

Electrical Specifications

Frequency and Gain Performance

Frequency Range (MHz)	Gain (dBi)	Vertical Beam Width
806-960	2±0.5	85°
1710-2500	4±1	55°
2500-2700	4±1	50°

Key Electrical Metrics

50 Ω

Input Impedance

50 W

Max CW Power

1.4

Max VSWR

Mechanical Specifications

Physical Dimensions

- Antenna Size: $\varnothing 204 \times 115$ mm
- Packing Size: 184x184x186mm
- Weight: 0.5kg

Connector

N-Female

Radome Material

ABS

Environmental Specifications

Operating Temperature Range	-40 to +70
Max Working Humidity	95 %
Application Environment	Indoor, Outdoor