

Internal Wiring Shielded Cable

This cable is suitable for internal wiring of electronic equipment. It is available in stranded and solid conductor types from 30 AWG to 16 AWG and features a spiral shield with bare or tinned copper conductors.

PE/PVC 内部屏蔽线		1354 AWM																																																																
Internal Wiring Shielded Cable																																																																		
■ 导体 1. 导体材料: 裸铜或镀锡铜 2. 导体结构: 绞合或实心	■ 绝缘 1. 绝缘材料: PVC 2. 绝缘厚度: 符合 UL 1354 标准																																																																	
<p>导体规格表</p> <table border="1"> <thead> <tr> <th>导体规格</th> <th>导体直径 (mm)</th> <th>导体截面积 (mm²)</th> <th>导体重量 (g/100m)</th> <th>绝缘厚度 (mm)</th> <th>总直径 (mm)</th> <th>重量 (g/100m)</th> </tr> </thead> <tbody> <tr> <td>16 AWG</td> <td>1.27</td> <td>1.27</td> <td>1.27</td> <td>0.15</td> <td>1.57</td> <td>1.27</td> </tr> <tr> <td>18 AWG</td> <td>1.02</td> <td>0.82</td> <td>0.82</td> <td>0.15</td> <td>1.32</td> <td>0.82</td> </tr> <tr> <td>20 AWG</td> <td>0.81</td> <td>0.52</td> <td>0.52</td> <td>0.15</td> <td>1.11</td> <td>0.52</td> </tr> <tr> <td>22 AWG</td> <td>0.64</td> <td>0.32</td> <td>0.32</td> <td>0.15</td> <td>0.93</td> <td>0.32</td> </tr> <tr> <td>24 AWG</td> <td>0.51</td> <td>0.20</td> <td>0.20</td> <td>0.15</td> <td>0.81</td> <td>0.20</td> </tr> <tr> <td>26 AWG</td> <td>0.40</td> <td>0.13</td> <td>0.13</td> <td>0.15</td> <td>0.70</td> <td>0.13</td> </tr> <tr> <td>28 AWG</td> <td>0.32</td> <td>0.08</td> <td>0.08</td> <td>0.15</td> <td>0.62</td> <td>0.08</td> </tr> <tr> <td>30 AWG</td> <td>0.25</td> <td>0.05</td> <td>0.05</td> <td>0.15</td> <td>0.55</td> <td>0.05</td> </tr> </tbody> </table>				导体规格	导体直径 (mm)	导体截面积 (mm²)	导体重量 (g/100m)	绝缘厚度 (mm)	总直径 (mm)	重量 (g/100m)	16 AWG	1.27	1.27	1.27	0.15	1.57	1.27	18 AWG	1.02	0.82	0.82	0.15	1.32	0.82	20 AWG	0.81	0.52	0.52	0.15	1.11	0.52	22 AWG	0.64	0.32	0.32	0.15	0.93	0.32	24 AWG	0.51	0.20	0.20	0.15	0.81	0.20	26 AWG	0.40	0.13	0.13	0.15	0.70	0.13	28 AWG	0.32	0.08	0.08	0.15	0.62	0.08	30 AWG	0.25	0.05	0.05	0.15	0.55	0.05
导体规格	导体直径 (mm)	导体截面积 (mm²)	导体重量 (g/100m)	绝缘厚度 (mm)	总直径 (mm)	重量 (g/100m)																																																												
16 AWG	1.27	1.27	1.27	0.15	1.57	1.27																																																												
18 AWG	1.02	0.82	0.82	0.15	1.32	0.82																																																												
20 AWG	0.81	0.52	0.52	0.15	1.11	0.52																																																												
22 AWG	0.64	0.32	0.32	0.15	0.93	0.32																																																												
24 AWG	0.51	0.20	0.20	0.15	0.81	0.20																																																												
26 AWG	0.40	0.13	0.13	0.15	0.70	0.13																																																												
28 AWG	0.32	0.08	0.08	0.15	0.62	0.08																																																												
30 AWG	0.25	0.05	0.05	0.15	0.55	0.05																																																												