

Male NPT Screwed Brass Camlock Coupling

This quick camlock connector is made from durable brass. It is suitable for use with oils, coolants and water.



ADDITIONAL IMAGES



Product Overview

High-Performance Brass Camlock Couplings

These professional-grade brass camlock couplings offer superior abrasion resistance and a durable, non-sparking design ideal for industrial fluid transfer. Engineered for high efficiency and safety, these connectors facilitate rapid hose and pipe connections without the need for specialized tools. They are the preferred choice for suction and discharge applications in sectors such as paint and ink manufacturing, as well as pump and tank operations.

Technical Specifications

Maximum Working Pressure

250 psi

Working Pressure

Material Composition	Forged Brass, Carbon Steel Plated Pins, NBR/BUNA/EPDM/VITON Seals
Available Sizes	1/2 inch to 6 inches
Operating Temperature	-101°C to +232°C (150°F to 450°F)

Standards & Compatibility

Compliance Standards

A-A-59326 • MIL-C-27487 • DIN 2828 • DIN 14420-7

Thread Options

- NPT
- BSPP
- BSPT

Usage Guidelines

Restricted Applications

For safety and performance integrity, this camlock coupling is strictly not suitable for the transfer of steam, compressed air, or pressurized liquid gases.