

MIG250S Inverter Gas Shielded Welding Machine

This welding machine is suitable for welding metal plates with a thickness above 0.8mm. It offers low cost, high efficiency, and improved welding quality with stable current due to self-compensation for voltage fluctuation.



Overview

Professional Performance

The MIG250S is a high-performance inverter gas shielded welding machine engineered for demanding industrial applications. Featuring precise voltage and current control, this unit ensures consistent weld quality across a variety of thicknesses. Its integrated wire feeder and mobile design provide the flexibility and efficiency required for professional welding environments.

Electrical Specifications

Input Voltage	220 V
Input Frequency	50/60Hz
Rated Input Power Capacity	8.4 KW
Rated Input Current	38.1 A

Performance Metrics

Key Performance Metrics

250 A

Max Output Current

60 %

Duty Cycle

85 %

Efficiency

Rated Output Voltage	26.5 V
No-Load Voltage	42 V

Welding Capabilities

Wire Feeder Details

Parameter	Value
Feeding Speed	2.5-13 m/min
Wire Feeder Type	Inside
Wire Diameter	0.8/1.0 mm
Coil Diameter	300 mm

Post-Gas Time	2 S
---------------	-----

Physical and Safety

Physical Dimensions & Weight

- Weight: 33 KG
- Dimensions: 604 x 298 x 529 mm

Protection Class

IP21

Insulation Class

Class B