

Motorcycle Tire Changer with Swing Arm

This motorcycle tire changer is designed for efficient and safe tire replacement. It features a robust construction with a swing arm design for easy tire mounting and demounting.



Overview

Professional Motorcycle Tire Changer

This swing arm motorcycle tire changer is a robust, semi-automatic solution designed for efficient tire replacement and inflation. Built with heavy-duty steel and featuring a high-frequency chrome-plated working head, it ensures exceptional durability and abrasion resistance. The machine is engineered to protect delicate rims during operation while providing precise, synchronous centering for smooth performance.

Design Highlights

Swing Arm Design, Protective Rim Guards, Hard Chrome Working Head, Synchronous Centering

Technical Specifications

Clamping Capabilities

10 inch

Outside Clamping Min

19 inch

Outside Clamping Max

12 inch

Inside Clamping Min

21 inch

Inside Clamping Max

Operating Metrics

Parameter	Value
Max Wheel Diameter	960mm
Tire Width Range	3-15 inches
Working Pressure	8-10 bar
Power Output	0.75kw / 1.1kw

Logistics

Packing Details

- Dimensions: 1130 x 790 x 900 mm
- Volume: 0.80 cbm
- Gross Weight: 212 kgs
- 20ft Container Capacity: 28 units
- 40ft Container Capacity: 60 units

Certifications

Standards Compliance

CE Certified