

Non-Rewirable Power Cord with Two-Pole Plug

This power cord features non-rewirable connectors and a two-pole plug without earthing contact. The power cords are rated at 250 Vac: 10A and are compatible with H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F & H05RN-F cables.



Overview

Professional Grade Power Solutions

This non-rewirable power cord features a two-pole plug design, engineered for reliable performance in demanding electrical environments. It supports a variety of cable types and is built to meet international safety standards, ensuring consistent power delivery for compatible equipment. Ideal for B2B applications requiring robust, pre-assembled connectivity solutions.

Technical Specifications

Electrical Ratings

10 A

Rated Current

250 V

Rated Voltage

Supported Cable Types

- H05VV-F 3G0.75
- H05VV-F 3G1.0
- H05RR-F 3G0.75
- H05RR-F 3G1.0
- H05RR-F 3G1.5
- H03VVH2-F 2x0.75
- H05VVH2-F 2x0.75
- H05VV-F 2x0.75

Compliance

Certifications & Marks

TUV • IRAM • IMQ • INMETRO

Standards Compliance

IRAM 2063:2009, IRAM-NM 60884-1:2006, ABNT NBR NM 60884-1/2004, NBR 14136/2007

Product Details

Model Variants

Model	Certification Number
YS-67	TUV 19.1961
YS-68	TUV 19.1962