

Non-Sparking Hook Wrench Spanner

This non-sparking wrench is designed for use in hazardous environments. It is suitable for applications in the petroleum, chemical, power generation, railroad, and mining industries to avoid creating sparks in explosive atmospheres.



Product Overview

Non-Sparking Hook Wrench Spanner

Designed for safety in hazardous environments, this non-sparking hook wrench is an essential tool for industries where flammable gases, liquids, or dusts are present. It is engineered to prevent sparks during strikes, collisions, or friction, making it ideal for use in petroleum, chemical, mining, and power generation sectors. The tool is available in two specialized alloys—Beryllium Copper and Aluminum Bronze—to ensure both safety and durability.

Key Features

Primary Applications	Petroleum Industry, Chemical Industry, Power Generation, Railroad, Mining
Function	Dismounting bearings and locknuts of various sizes

Technical Specifications

Material Alloys

Beryllium Copper (Be-Cu) • Aluminum Bronze (Al-Cu)

Size and Weight Specifications

No.	Size Range (mm)	Length (mm)	Al-Cu Weight (g)	Be-Cu Weight (g)
101	22-26	135	45	58
102	28-32	148	72	85
103	34-36	166	105	120
104	38-42	178	125	143
105	45-52	190	178	205