

Open-Air Electric Shuttle Vehicle

This electric shuttle is designed for transporting passengers in resorts and parks. It features multiple rows of seating, an open-air design, and quiet, emission-free operation.



ADDITIONAL IMAGES



Overview

Premium Electric Sightseeing Shuttle

This luxury electric sightseeing vehicle is designed to provide a comfortable and eco-friendly passenger experience in hotels, parks, and educational campuses. Featuring an open-air design, it is available in various seating configurations including 8, 11, 14, and 23-seat options. With flexible power system choices between DC and AC, this shuttle delivers reliable performance tailored to specific operational requirements.

Performance

Key Performance Metrics

28 km/h
Max Speed

100 km
Range

15 %
Climbing Ability (DC)

25 %
Climbing Ability (AC)

Technical Specifications

Dimensions

Dimension	Value
Length x Width x Height	4965 x 1520 x 1970 mm
Axle Distance	2650 mm
Front Tread	1280 mm
Rear Tread	1270 mm
Min. Clearance	150 mm

Weight & Capacity

- Passenger Capacity: 14 seats
- Kerb Weight: 1260 kg
- Gross Weight: 2450 kg

Powertrain System

5kW DC Motor, 7.5kW AC Motor, 6V x 12pcs Battery

Operational Details

Operational Specs

- Charging Time: 8–10 hours
- Min Turning Radius: 6.5 meters
- Braking Distance: d4.5 meters

Color Options

Orange • Yellow • Blue • Green • Pink