

Petroleum Products Aniline Point Tester

This aniline point tester determines the lowest temperature at which a light petroleum product sample and aniline will dissolve into a single liquid phase. The instrument uses an electric heater to heat the sample, manually adjusts the controlling temperature, and stirs the sample using a stepless speed regulation motor, with automatic endpoint detection and sound/light alarms.



Product Overview

Precision Aniline Point Testing

The PT-D611-262 Aniline Point Tester is engineered for accurate determination of the aniline point in petroleum products, identifying the lowest temperature at which a sample and aniline dissolve into a single liquid phase. Designed in strict compliance with GB/T262 and ASTM D611 standards, this instrument ensures reliable results for quality control and research applications. It features manual temperature control, a variable speed stirring motor, and an automated end-point detection system with audible and visual alarms for enhanced operational efficiency.

Technical Specifications

Measurement Range

150 °C

Max Temperature

Power Supply	AC 220V±10%, 50 Hz
Heating Power	25 W
Stirring Speed	0 - 1200 r/min

Dimensions and Build

Device Dimensions	360mm x 250mm x 545mm
-------------------	-----------------------

Standards and Compliance

Standards Compliance	GB/T262, ASTM D 611
----------------------	---------------------

Operational Features

Key Operational Features

- Manual temperature control
- Stepless speed regulation motor
- Automated end-point detection
- Audible and visual alarm system