

# Pneumatic Tank Bottom Diaphragm Valve

This pneumatic tank bottom diaphragm valve is designed for sterile and aseptic processes. Its diaphragm isolates the process fluid from the valve actuator, which prevents contamination.



## ADDITIONAL IMAGES



## Product Overview

### Aseptic Tank Bottom Solution

The Pneumatic Tank Bottom Diaphragm Valve is engineered specifically for discharging media from tanks without leaving residue in the chamber. Designed for sterile and aseptic processes, this valve ensures process isolation from the actuator to prevent contamination. Its robust construction makes it an ideal choice for critical applications in the pharmaceutical, biotechnology, and food and beverage industries.

## Technical Specifications

### Operating Temperature

**150 °C**

Max Temp (Stainless Actuator)

**130 °C**

Max Temp (Plastic Actuator)

### Size Range

1" - 4" (DN25 - DN100)

### Connection Options

Weld, Clamp, Flange, Thread

## Materials & Construction

### Body Material

- Forged: 1.4404 / 316L / 1.4435 NB2
- Cast: 1.4404 / 316L

### Diaphragm Materials

EPDM + PTFE, EPDM, Silicon, FPM (Viton)

## Compliance & Certification

### Certifications

3A-54-02 / 1580 • PED 97/23 EC • FDA 177.2600

## Performance Data

### Pressure Ratings (Unidirectional)

Configuration	Rubber (bar)	PTFE (bar)
Normally Closed (Standard)	6	4.5
Normally Closed (Option)	8	6
Normally Open / Double Acting	8	6